


SKINTOP® ST-HF-M

SKINTOP® halogen-free



SKINTOP® ST-HF-M

■ Benefits

- Maximum reliability
- Extremely flame retardant according to UL 94 V0
- Completely halogen-free (inclusive seal material)
- Self extinguishing, no dripping
- Permanent vibration protection

■ Application range

- Where personal and property protection is a priority.
- Public buildings
- Ventilation systems
- Tunnel construction
- Underground railways and trains

■ Approvals (Norm references)



■ Design

- Metric connection thread acc. to EN 50262

■ Technical data



Caution
Installation dimensions and tightening torques see Appendix T21



Colour delivered
RAL 7035 light grey



Material
Polyamide UL94 V0 - halogen-free
Seal: LSE 1 - halogen-free
O-ring: LSE 1 - halogen-free

Tests

Filament wire test
EN 60695-2-1/1
+960 °C



Degree of protection
IP 68 - 5 bar



Range of temperature
-20 °C up to +100 °C

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® ST-HF-M						
53111407	ST-HF-M 12 x 1,5	4-5,5	15	30,0	8,0	100
53111417	ST-HF-M 16 x 1,5	4,5-9	19	34,0	8,0	100
53111427	ST-HF-M 20 x 1,5	7-13	25	37,0	9,0	100
53111437	ST-HF-M 25 x 1,5	9-17	30	40,0	10,0	50
53111447	ST-HF-M 32 x 1,5	11-21	36	47,0	10,0	25
53111457	ST-HF-M 40 x 1,5	19-28	46	52,0	10,0	10
53111467	ST-HF-M 50 x 1,5	27-35	55	62,0	12,0	5
53111477	ST-HF-M 63 x 1,5	34-45	66	71,0	12,0	5

■ Accessories

- SKINTOP® GMP-HF-M see page 661