


New

SKINTOP® CLICK BS



Info

- The most innovative cable insertion system on the market for very fast, highly flexible assembly. Simply click in - turn to left - turn to right - finished. Result: fixed, centred, strain relieved and maximum protection class in seconds.

SKINTOP® CLICK BS

Benefits

- Reliable bending protection for cable conservation and functional reliability
- Up to 70% time saving due to innovative CLICK system
- No thread required
- To protect flexible cables
- Fewer parts, counter nut no longer needed

Application range

- Cables for electrical appliances and machinery, which are moved under normal use, must be protected against excessive bending, as required in accordance with VDE 0730.
- Robotics industry
- Flexing machine parts
- Apparatus construction
- Light and sound applications

Approvals (Norm references)



Scope of delivery

- Disassembly tool contained in the delivery scope

Technical data

RAL	Colour delivered RAL 7001 silver-grey RAL 7035 light grey RAL 9005 black / UV resistant
Material	Body: special polyamide Seal: special elastomer
IP	Degree of protection IP 68 - 4 bar (M12) IP 68 - 5 bar (M16 - M32)
Temperature	Range of temperature -20 °C up to +100 °C

Part number	Part designation / size	Clamping range ØF mm	M (hole mm)	SW1 / SW2 mm	Overall length C mm	Thread length D mm	S (wall thickness mm)	Pieces / PU
SKINTOP® CLICK BS light grey								
53112932	CLICK BS 12	3,5-7	12,3 (-0,2)	15 / 18	74,0	8,0	1,0 - 4,0	50
53112888	CLICK BS 16	5-9	16,3 (-0,2)	19 / 22	94,0	8,0	1,0 - 4,0	50
53112889	CLICK BS 20	7-13	20,3 (-0,2)	19 / 22	108,0	8,0	1,0 - 4,0	25
53112890	CLICK BS 25	9-17	25,3 (-0,2)	30 / 34	127,0	8,0	1,0 - 4,0	25
53112933	CLICK BS 32	11-21	32,3 (-0,2)	36 / 40	155,0	8,0	1,0 - 4,0	25
SKINTOP® CLICK BS silver grey								
53112934	CLICK BS 12	3,5-7	12,3 (-0,2)	15 / 18	74,0	8,0	1,0 - 4,0	50
53112906	CLICK BS 16	5-9	16,3 (-0,2)	19 / 22	94,0	8,0	1,0 - 4,0	50
53112907	CLICK BS 20	7-13	20,3 (-0,2)	19 / 22	108,0	8,0	1,0 - 4,0	25
53112908	CLICK BS 25	9-17	25,3 (-0,2)	30 / 34	127,0	8,0	1,0 - 4,0	25
53112935	CLICK BS 32	11-21	32,3 (-0,2)	36 / 40	155,0	8,0	1,0 - 4,0	25
SKINTOP® CLICK BS black								
53112936	CLICK BS 12	3,5-7	12,3 (-0,2)	15 / 18	74,0	8,0	1,0 - 4,0	50
53112909	CLICK BS 16	5-9	16,3 (-0,2)	19 / 22	94,0	8,0	1,0 - 4,0	50
53112911	CLICK BS 20	7-13	20,3 (-0,2)	19 / 22	108,0	8,0	1,0 - 4,0	25
53112912	CLICK BS 25	9-17	25,3 (-0,2)	30 / 34	127,0	8,0	1,0 - 4,0	25
53112937	CLICK BS 32	11-21	32,3 (-0,2)	36 / 40	155,0	8,0	1,0 - 4,0	25