


SKINDICHT® KU, KUS, KUK



1
SKINDICHT® KU, KUS, KUK

2

3

■ **Benefits**

- Enables the use of cable glands with smaller connection threads than the existing threaded holes
- Glas fibre reinforced for maximum mechanical stability

■ **Application range**

- Machines
- Devices
- Housings

■ **Approvals (Norm references)**



■ **Design**

- PG connection thread

■ **Design**

- SKINDICHT® KU with hexagon and flat design
- SKINDICHT® KUS with hexagon and larger height
- SKINDICHT® KUK with knurled heads

■ **Technical data**

RAL	Colour delivered RAL 7035 light grey
	Material Polyamide, glass fibre reinforced
	Range of temperature KU, KUS: -40°C up to +100°C KUK: -20°C up to +80°C

Part number	Part designation / size Outer / inner	Pieces / PU
SKINDICHT® KU		
51730010	KU 11/7	50
52025100	KU 13,5/7	50
52025110	KU 16/9	50
52025120	KU 21/11	25
51730040	KU 21/13,5	25
52025130	KU 29/13,5	25
51730050	KU 29/16	25
52025140	KU 36/16	25
52025150	KU 36/21	25
52025050	KU 36/29	25
52025160	KU 42/21	25
52025170	KU 42/29	25
52025060	KU 42/36	25
52025180	KU 48/29	25
52025190	KU 48/36	25
52025070	KU 48/42	25
SKINDICHT® KUS		
52025040	KUS 9/7	50
51730060	KUS 11/9	50
51730070	KUS 13,5/11	50
51730080	KUS 16/13,5	50
SKINDICHT® KUK		
51730020	KUK 13,5/9	50
51730025	KUK 16 /9	50
51730030	KUK 16/11	50
51730035	KUK 21/13,5	50
51730090	KUK 21/16	50
51730100	KUK 29/21	25
51730110	KUK 36/29	25