

SKINDICHT® E



Benefits

- One seal for several clamping ranges
- Rings can be individually adapted to various cable diameters

Application range

- Incised sealing ring for SKINDICHT® cable glands

Approvals (Norm references)



Note

- Delivery will be in max. possible packing unit, minimum order quantity is one packing unit

Technical data

| | |
|-----------------------------|-------------------|
| Colour delivered | Black |
| Material | CR |
| Range of temperature | -20°C up to +80°C |

| Part number | Part designation / size | Outer diameter x bores mm | Thickness in mm | Pieces / PU |
|---------------------|-------------------------|---------------------------|-----------------|-------------|
| SKINDICHT® E | | | | |
| 52005780 | E 9 | 13,5 x 5/8 | 5.5 | 250 |
| 52003690 | E 11 | 16,5 x 7/10/12,5 | 6.0 | 250 |
| 52003700 | E 13,5 | 18,5 x 7/10,5/13/16 | 6.5 | 250 |
| 52003710 | E 16 | 20,5 x 8/10,5/13,5/16 | 7.5 | 250 |
| 52003720 | E 21 | 26,0 x 11/15/18/20 | 8.0 | 100 |
| 52003730 | E 29 | 35,0 x 19/23/27/31 | 9.5 | 100 |
| 52003740 | E 36 | 45,0 x 25/28/31/35 | 12.0 | 50 |
| 52005790 | E 42 | 52,0 x 35,5/39/42,5/46 | 14.0 | 50 |
| 52005800 | E 48 | 57,0 x 40,5/44/47/50,5 | 14.0 | 50 |

Benefits

- One seal for several clamping ranges
- Rings can be individually adapted to various cable diameters
- For high temperatures
- Resistant against oils, solvents, acids and chemicals

Application range

- Incised sealing ring made of VITON® for SKINDICHT® cable glands

Approvals (Norm references)



Note

- Delivery will be in max. possible packing unit, minimum order quantity is one packing unit

Technical data

| | |
|-----------------------------|--------------------|
| Colour delivered | red brown |
| Material | FKM |
| Range of temperature | -10°C up to +200°C |



| Part number | Part designation / size | Outer diameter x bores mm | Thickness in mm | Pieces / PU |
|----------------------|-------------------------|---------------------------|-----------------|-------------|
| SKINDICHT® EV | | | | |
| 52010340 | EV 11 | 7/10/12,5 | 6.0 | 50 |
| 52010350 | EV 13,5 | 7/10,5/13/16 | 6.5 | 50 |
| 52010360 | EV 16 | 8/10,5/13,5/16 | 7.5 | 50 |
| 52010370 | EV 21 | 11/15/18/20 | 8.0 | 25 |
| 52010380 | EV 29 | 19/23/27/31 | 9.5 | 25 |
| 52010390 | EV 36 | 25/28/31/35 | 12.0 | 25 |
| 52010410 | EV 42 | 35,5/39/42,5/46 | 14.0 | 25 |

Viton® is a registered trademark of DuPont de Nemours

SKINDICHT® O-Ring Perbunan® PG



Benefits

- Resistant against oil, dust and water

Application range

- Used for reliable sealing against oil, dust and water at the connection thread of a gland or similar components.

Approvals (Norm references)



Note

- Delivery will be in max. possible packing unit, minimum order quantity is one packing unit

Technical data

| | |
|-----------------------------|---|
| Colour delivered | Black |
| Material | NBR |
| Range of temperature | Ozone- and UV-resistant -20°C up to +100°C |