



ÖLFLEX® PLUG Extension Cable 540 P safety yellow*

Earthing-type extension cable with straight plug and coupling



Application range

- Mechanical engineering
- Construction industry
- Agricultural equipment
- In damp interiors or outdoors

Product features

- Other lengths, customised versions, cable types and plug versions are available upon request

Product Make-up

- Mounted, straight earthing-type plug (16 amp., 250 V, solid rubber, colour: black) in accordance with DIN 49440/441, protection rating: IP 44
- Mounted, straight earthing-type coupling with rubber cover (16 A, 250 V, solid rubber, colour: black) in accordance with DIN 49440/441, protection rating: IP 44

Technical data

	ETIM 5.0 Class-ID: EC001576 ETIM 5.0 Class-Description: Power cord
	Nominal voltage U ₀ : 250 V AC

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Length (m)	Copper index kg/1.000 pieces
ÖLFLEX® PLUG Extension Cable 540 P safety yellow*				
73222337	3 G 1.5	8.9	5	215.0
73222322	3 G 1.5	8.9	10	430.0
73222375	3 G 1.5	8.9	15	645.0
73222323	3 G 1.5	8.9	25	1075.0
73222324	3 G 1.5	8.9	50	2150.0
73222385	3 G 2.5	10.6	5	360.0
73222325	3 G 2.5	10.6	10	720.0
73222386	3 G 2.5	10.6	15	1080.0
73222326	3 G 2.5	10.6	25	1800.0
73222327	3 G 2.5	10.6	50	3600.0

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

* Trade product, no Lapp product

Photographs are not to scale and do not represent detailed images of the respective products.