



UNITRONIC® LiYCY (TP)

Screened data transmission cable with colour code acc. to DIN 47100 and twisted pairs

LAPP KABEL STUÏGART UNITRONIC LiYCY (TP)



Info

- TP = twisted pair

Benefits

- Decoupling of circuits by means of twisted-pair (TP) design (crosstalk effects)
- Overall braid minimises electrical interference

Application range

- Can be used multifunctional in electronics of computer systems, electronic control equipment, office machines, balances, etc.
- Dry or damp rooms

Product features

- Good protection against capacitive interference from electric fields (e.g. power cable)
- Flame-retardant according IEC 60332-1-2

Norm references / Approvals

- Based on VDE 0812

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

Technical data



Classification

ETIM 5.0 Class-ID: EC000830
ETIM 5.0 Class-Description: Data cable



Core identification code

DIN 47100, refer to Appendix T9



Mutual capacitance

C/C: approx. 120 nF/km
C/S: approx. 160 nF/km



Peak operating voltage

(not for power applications)
at 0.14 mm²: 350 V
at ≥ 0.25 mm²: 500 V



Inductivity

approx. 0.65 mH/km



Conductor stranding

Fine copper wire strands



Minimum bending radius

Occasional flexing: 15 x outer diameter
Fixed installation: 6 x outer diameter



Test voltage

At 0.14 mm²: 1200 V

Temperature range

Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Article number	Dimension and cross section in mm ²	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiYCY (TP)				
0035131	2 x 2 x 0,14	5.3	18.5	39
0035141	3 x 2 x 0,14	5.8	23	48
0035132	4 x 2 x 0,14	6.2	26.6	54
0035133	6 x 2 x 0,14	7.1	48.5	85
0035150	8 x 2 x 0,14	8.2	53.7	97
0035134	10 x 2 x 0,14	8.7	59	110
0035135	12 x 2 x 0,14	8.9	66	142
0035136	16 x 2 x 0,14	10.2	79	154
0035142	20 x 2 x 0,14	11.3	97	184
0035137	25 x 2 x 0,14	12.5	113	238
0035800	2 x 2 x 0,25	6.3	28	54
0035801	3 x 2 x 0,25	7.1	39.6	68.5
0035802	4 x 2 x 0,25	7.6	44.9	81
0035803	6 x 2 x 0,25	8.5	69.5	115
0035804	8 x 2 x 0,25	10.3	76.9	130
0035805	10 x 2 x 0,25	11	102	158
0035806	12 x 2 x 0,25	11.3	120	190
0035807	16 x 2 x 0,25	12.5	146.5	238

Article number	Dimension and cross section in mm ²	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0035808	25 x 2 x 0,25	16.1	205	344
0035810	2 x 2 x 0,5	7.9	48.1	93
0035811	3 x 2 x 0,5	8.7	73.7	129
0035812	4 x 2 x 0,5	9.4	82	146
0035813	6 x 2 x 0,5	11.1	110	198
0035814	8 x 2 x 0,5	13.1	139	259
0035816	12 x 2 x 0,5	14.9	198.3	354
0035817	16 x 2 x 0,5	16.5	240	459
0035820	2 x 2 x 0,75	8.5	58	106
0035821	3 x 2 x 0,75	9.4	84	140
0035822	4 x 2 x 0,75	10.7	108	179
0035827	5 x 2 x 0,75	11.1	126	215
0035823	6 x 2 x 0,75	12.1	146	246
0035824	8 x 2 x 0,75	14.7	180	305
0035825	12 x 2 x 0,75	16.2	261	456
0035830	2 x 2 x 1	9	84	142
0035831	3 x 2 x 1	10.4	96	173
0035832	4 x 2 x 1	11.3	121	212
0035836	5 x 2 x 1	11.8	161	266

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- UNITRONIC® CY PiDY (TP) refer to page 286
- UNITRONIC® PUR CP (TP) refer to page 290
- UNITRONIC® Li2YCY (TP) fine-wire refer to page 291
- UNITRONIC® LiYCY (TP) A refer to page 302

Accessories

- SKINTOP® MS-SC-M refer to page 732
- Multipurpose shears A and B refer to page 998
- STAR STRIP stripping tool refer to page 1000